

```

/* SplayTree.h
 * Tahmid Rahman
 * Dylan Jeffers
 *
 * This is the header file
 * for SplayTree
 */

#ifndef SPLAYTREE_H_
#define SPLAYTREE_H_

#include "BST.h"
#include "pair.h"
#include "library/queue.h"
#include <iostream>

using namespace std;

// Forward declaration of SplayTreeNode class
template <typename K, typename V> class SplayTreeNode;

template<typename K, typename V>
class SplayTree: public BST<K,V> {
private:
    int size;
    SplayTreeNode<K,V>* root;

public:
    SplayTree();
    ~SplayTree();

    /* All public functions declared/detailed in BST.h */
    /* The following methods are defined in SplayTree-inl.h */
    int getSize();
    bool isEmpty();
    int getHeight();
    K getMax();
    K getMin();

    /* dictionary operations */
    void insert (K key, V value);
    void update (K key, V value);
    bool contains (K key);
    void remove (K key);
    V find (K key);

    /* traversal operations */
    Queue< Pair<K,V> >* getPreOrder();
    Queue< Pair<K,V> >* getInOrder();
    Queue< Pair<K,V> >* getPostOrder();
    Queue< Pair<K,V> >* getLevelOrder();
    K getRootKey();

private:
    /*declarations of our internal private methods */
    SplayTreeNode<K,V>* insertInSubtree(SplayTreeNode<K,V>* current, K key, V
value, bool* inserted, bool* skip);

    void updateInSubtree(SplayTreeNode<K,V>* current, K key, V value);

```

```

    SplayTreeNode<K,V>* removeFromSubtree (SplayTreeNode<K,V>* current, K key);
    bool containsInSubtree (SplayTreeNode<K,V>* current, K key, bool * skip);
    K getMaxInSubtree(SplayTreeNode<K,V>* current);
    K getMinInSubtree(SplayTreeNode<K,V>* current);
    void buildPreOrder (SplayTreeNode<K,V>* current, Queue< Pair<K,V> >* it);
    void buildInOrder (SplayTreeNode<K,V>* current, Queue< Pair<K,V> >* it);
    void buildPostOrder(SplayTreeNode<K,V>* current, Queue< Pair<K,V> >* it);
    void traverseAndDelete (SplayTreeNode<K,V>* current);

    SplayTreeNode<K,V>* splay(SplayTreeNode<K,V>* current, K key);
    int getHeightOfSubtree(SplayTreeNode<K,V>* current);

    /* the six rotations needed to fix each of the six imbalances*/

    SplayTreeNode<K,V>* rightRotate(SplayTreeNode<K,V>* current);
    SplayTreeNode<K,V>* leftRotate(SplayTreeNode<K,V>* current);

    SplayTreeNode<K,V>* rightLeftRotate(SplayTreeNode<K,V>* current);
    SplayTreeNode<K,V>* leftRightRotate(SplayTreeNode<K,V>* current);

    SplayTreeNode<K,V>* rightRightRotate(SplayTreeNode<K,V>* current);
    SplayTreeNode<K,V>* leftLeftRotate(SplayTreeNode<K,V>* current);
};

```

```

/* SplayTreeNode is templated class that stores data for each node in the
SplayTree */

```

```

template <typename K, typename V>
class SplayTreeNode {
    private:
        K key;
        V value;

        /*using parent implementation vs record implementation (ask me if
        if you're unsure what this means */
        SplayTreeNode<K,V> * left;
        SplayTreeNode<K,V> * right;

        SplayTreeNode();
        SplayTreeNode(K k, V v);
        int getHeight();
    //so SplayTree can directly access private aspects of this class
    friend class SplayTree<K,V>;
};

```

```

#include "SplayTree-inl.h"
#include "SplayTree-private-inl.h"

```

```
#endif
```